



UniRac Side of Pole Mount Series 4002

UniRac®

Side-of-Pole Mounts

UniRac mounting structures incorporate SolarMount slotted rails that fit most PV modules on the market and are manufactured of clear anodized (rails and legs) aluminum to withstand corrosion.

Features include:

- 120 mph wind load design
- PV module mounting hardware and U-Bolts for pole mounting are included
- Stainless steel hardware
- 1-year limited warranty
- Adjustable tilt 15° to 60°
- Models mount 1-4 PV modules
- Ships UPS



Series 4011

*Order 1 extra module bolt. ** Order 2 extra module bolts.

Part #	Model	Rail /Channel Length	Pipe Size (sch 40)	Weight	Part #	Model	Rail /Channel Length	Pipe Size (sch 40)	Weight
963303	400111	22"/24"	2 1/2	6	963028	400230	96"/40"	4	30
963UNIUPS26XXL	400204	28"/30"	2 1/2	12	963027	400231	104"/32"	4	32
963UNIUPS32M	400206	32"/25"	2 1/2	15	963272	400232*	108"/40"	4	35
963305	400207	32"/35"	2 1/2	16	963306	400233	56"/40"	3	24
963214	400209	40"/35"	2 1/2	20	963030	400236	28"/40"	2 1/2	15
963SP75USP2MA	400211	44"/25"	2 1/2	20	963031	400237	32"/40"	2 1/2	15
963UNIUPS52L	400212	52"/32"	3	21	963026	400238	36"/30"	2 1/2	19
963020	400214	52"/40"	3	22	963367	400239	38"/30"	2 1/2	20
963UNIUPS60L	400215	60"/32"	3	24	963307	400244	64"/32"	3	24
963UNIUPS64XL	400219	64"/40"	3	25	963432	400246	104"/40"	4	34
963UNIUPS80L	400222	80"/32"	4	25	963308	400247	98"/24"	4	28
963033	400224	80"/40"	4	27	963371	400249	72"/40"	4	30
963UNIUPS88L	400226	88"/32"	4	26	963309	400250	66"/24"	3	24
963228	400227	88"/24"	4	26	963312	400257	26"/35"	2 1/2	14
963430	400228	96"/32"	4	27	963313	400259	92"/32"	4	35

*Ships truck freight.

Model # Selection Guide

Module/Quantity	1	2	3	4
Mitsubishi 110	400257	400214	400224	400246
Mitsubishi 125	400207	400219	400230	–
Mitsubishi 175/180	400237	400219	400230	–
Sanyo 190/195/200	400239	400249	–	–
Sharp 130	400236	400233	400224	400232
Sharp 170/175	400238	400250	400247	–
Sharp 208/216/224	400209	400224	–	–
SunWize 85/90	400204	400212	400222	400259
Yingli 85	400111	400211	400250	400227



Series 4001